



#32 WOOD

Specialized Woodworking Applications

STRAIGHTER, EASIER CUTTING

Manufactured with a heavier gauge (.032") flexible carbon steel material

DESIGNED FOR CONTOUR CUTTING OF WOOD


Perfect for furniture manufacturing operations

*Note: Not recommended for blades shorter than 15' (4500mm) long.
If shorter blade is required, LENOX Flex Back is recommended*



WIDTH X THICKNESS		TOOTH FORM					
		RAKER SET			ALTERNATE		
IN	MM	TPI			TPI		
		2	3	4	2	3	4
1/4 x .032	6.4 x 0.80			◆			◆
3/8 x .032	9.5 x 0.80		◆	◆	◆	◆	◆
1/2 x .032	12.7 x 0.80	◆	◆	◆		◆	

APPLICATION



Wood

FRICITION BAND

Friction Cutting Operations

FAST CUTTING

Special set design for increased frictional heat

LONG LASTING


Special silicon carbon steel provides extended fatigue life

*Note: Operates at band speeds up to 20,000 feet per minute
(6,000 meters per minute)*



WIDTH X THICKNESS		TOOTH FORM
		STANDARD LENOX SET
IN	MM	TPI
		10
1 x .035	25.4 x 0.90	◆

APPLICATION



Ferrous metals